

PRO 9585C3B-PA – NAUJA!! PILNŲ SPALVŲ 8MP 4K 2,8-12mm Motorizuota 3-in-1 Aktyvioji Atgrasinimo Turret Kamera



Alarm Inputs / Relay Outputs	1CH alarm input; 1CH alarm output
Audio Inputs	1CH audio input; 1CH audio output; 1CH built-in speaker; 1CH built-in microphone
BLC	Yes
BLC/SSDR (WDR)	120dB
DNR	2D/3D DNR
Dimensions	Ø111.5 × 99.6
IR Illumination	IR range: 30 ~ 40 m White light range: 30 ~ 40 m
Image Quality	4K 8MP
Image Sensor (CCD)	1 / 1.8" CMOS
Lens	2.8~12mm@F1.4
Lens Mount	Φ14

Minimum Illumination – Colour	0.006lux@F1.4,AGC ON, 0 lux with IR 0 lux with White Light
Minimum Illumination – Mono	0.006lux@F1.4,AGC ON, 0 lux with IR 0 lux with LED
Operating Temperature	– 30 °C ~ 65°C
P0E	Yes
Power Consumption	< 12.5W
Resolution (Best)	8MP(3840×2160)
S/N Ratio	≥50dB
Shutter	1 / 2s ~ 1 / 100000 s
Storage Media & Capacity	Built-in micro SD card slot; up to 256GB
Weight(Cameras)	Approx. 0.64KG