

PRO 8443IS2 – 4 colių 4MP 25X tinklo
100 m infraraudonųjų spindulių
greitojo domo kamera, išmanus sekimas,
DC12V/PoE+, IP66, -30~55, įskaitant
maitinimo adapterį ir laikiklį.



DNR	Auto/Manual
Dimensions	Φ 173mm × 247mm (6.8" Φ × 9.7")
Enhancement	HLC, BLC, DWDR
IR Illumination	Color 0.01Lux @ (F1.65 AGC ON) B/W 0.002Lux @ (F1.65 AGC ON); 0Lux with IR
Image Sensor (CCD)	1/2.5" progressive scan CMOS
Lens (Optical)	f=4.8-120mm lens, 25x optical
Operating Temperature	-30°C ~ 55°C (-22°F ~ 131°F), 90%RH less (non-condensing), Cold start at - 20°C
POE	POE+
Power	DC12V or PoE+ (802.3.at, class 3), (Max 22W, include IR on, Heater on, Fan working)

Resolution (Best)	2560 × 1440
Shutter	1/1 s – 1/100,000 s
Storage Media & Capacity	SD card slot inside, support microSD/SDHC/SDXC, up to 256G
Weight(Cameras)	Approx. 2.1 Kg (13.22 lb.)
Within Range of IR LEDs	100m