

**PRO 9453E2A-AZ – 5 Megapikselių
motorizuotas priartinimas 2,8–12 mm
automatinis fokusavimas H265 / H264
realaus laiko išorinė IP kulkos
stiliaus kamera**



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	True WDR
Connection Cable	DC + POE / Video / Audio (RJ45)
DNR	2D + 3D
Dimensions	279.5mm × 100.3mm × 88.9mm
Dual Streaming	3 Streams

Effective Pixel	2592(H) x 1944(V)
Enhancement	Yes
Gamma Correction	0.45
Image Sensor (CCD)	1/3" CMOS 5MP
Lens	2.8~12mm Megapixel Auto Focus Day / Night ICR Lens
Minimum Illumination – Colour	0.036 lux @F2.0, AGC ON; 0.013 lux @ F1.2, AGC ON; 0 lux with IR
Minimum Illumination – Mono	0 Lux with IR LED's on
Model	IPC9453E2A-AZ
P0E	Yes
Power Consumption	<7W
Power Source	12V DC Regulated or P0E
Privacy	Yes
RS485 Interface	Yes
S/N Ratio	52db +
Scanning System	Yes
Shutter	1/25s ~ 1/100000s
Storage Media & Capacity	Network remote storage; micro SD card storage
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP and BNC
Within Range of IR LEDs	50-70m
Zoom	Yes – Auto