

PRO 9462S3A-AZ – 6 Megapikselių
varomasis priartinimas 2,8–12 mm
automatinio fokusavimo H265 / H264
išorinė IP mini kulšos stiliaus kamera



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Connection Cable	DC + POE / Video / Audio (RJ45)
DNR	2D + 3D
Dimensions	217.7 × 80.5 × 80.5
Dual Streaming	3 Streams
Effective Pixel	(3072 × 2048)
Enhancement	Yes

Gamma Correction	0.45
Image Sensor (CCD)	1/3" CMOS 6MP
Lens	2.8-12mm Megapixel Auto Focus Day / Night ICR Lens
Minimum Illumination – Colour	0.036 lux @F2.0, AGC ON; 0.013 lux @ F1.2, AGC ON; 0 lux with IR
Minimum Illumination – Mono	0 Lux with IR LED's on
Model	IPC9462S3A-AZ
P0E	Yes
Power Consumption	<7W
Power Source	12V DC Regulated or P0E
Privacy	Yes
RS485 Interface	Yes
S/N Ratio	52db +
Scanning System	Yes
Shutter	1/25s ~ 1/100000s
Storage Media & Capacity	Network remote storage; micro SD card storage
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP
Within Range of IR LEDs	30-50m
Zoom	Yes – Auto