

PRO 9483E3 – 4K 8 Megapikselių 2,8–12 mm varomas priartinimo H265 / H264
Realaus laiko IP bullet tipo kamera –
veido atpažinimas



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC/SSDR (WDR)	True WDR
Connection Cable	DC + POE / Video / Audio (RJ45)
DNR	2D + 3D
Dimensions	279.5 × 100.3 × 88.9
Dual Streaming	3 Streams
Effective Pixel	3840 × 2160
Enhancement	Yes
Gamma Correction	0.45

Image Sensor (CCD)	1 / 2.8" CMOS
Lens	2.8~12mm Megapixel Auto Focus Day / Night ICR Lens
Minimum Illumination – Colour	0.01lux@F1.2, AGC ON
Minimum Illumination – Mono	0 Lux with IR LED's on
P0E	Yes
Power Source	12V DC Regulated or P0E
Privacy	Yes
RS485 Interface	Yes
S/N Ratio	52db +
Scanning System	PAL
Shutter	1/25s ~ 1/100000s
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP and BNC
Within Range of IR LEDs	50m