

PRO 9544C3B-PA – NAUJA!! PILNAS SPAUDA 4MP 2,8 mm fiksuoto objektyvo 3-1 aktyvi atgrasinimo bokšto kamera



Audio Inputs	1CH audio input; 1CH built-in speaker; 1CH built-in MIC
BLC	Yes
BLC/SSDR (WDR)	120dB
Color	Grey or White
Compression Method	Main stream: H.265+ / H.265 / H.264+ / H.264
DNR	2D/3D DNR
Dimensions	Φ 94.6 × 82.8
Image Quality	4MP
Image Sensor (CCD)	1 / 3" CMOS
Lens	Fixed Iris 2.8 mm@F1.6, H.FoV:96°; V.FoV:54.5°; D.FoV:113°
Lens Mount	M12

Operating Temperature	– 30 °C ~ 60 °C
P0E	Yes
Power	P0E or DC12V
Power Consumption	< 9.5W
Resolution (Best)	4MP
S/N Ratio	≥50dB
Shutter	1 / 3s ~ 1 / 100000 s
Speaker	Built-in
Storage Media & Capacity	Built-in micro SD card slot; up to 256GB
Weight(Cameras)	Approx. 0.47KG
Within Range of IR LEDs	20-30m IR , 20-20m White Light