

**PRO 9544E3B – 2,8 mm 4MP super mažai
šviesos realaus laiko H.265 įmontuotas
garso IP mini akies rutulys su IR LED,
WDR, daugiasrautis srautas, POE**



AES	Yes
AGC	Auto
Audio Inputs	1CH audio input; 1 CH built-in MIC
BLC	Yes
BLC/SSDR (WDR)	120dB
DNR	3D DNR
Dimensions	Φ 94.6 × 82.8
Image Sensor (CCD)	1 / 3 „CMOS
Lens	2.8 mm@F1.6, horizontal FoV: 100.4°; vertical FoV: 68°; diagonal FoV:108°
Lens Mount	M12
Minimum Illumination – Colour	0.005 lux@F1.6, 0.0028 lux@F1.2
Minimum Illumination – Mono	0 lux with IR

Operating Temperature	– 30 °C ~ 60 °C (-22°F~140°F)
P0E	Yes , IEEE802.3af
Power Consumption	< 7.5W
Power Source	DC12V/PoE
Resolution (Best)	4MP 2592 × 1520
Shutter	Electronic Shutter 1 / 30 s ~ 1 / 100000 s
Storage Media & Capacity	Built-in micro SD card slot; up to 128GB
Weight(Cameras)	Approx. 0.46KG
Within Range of IR LEDs	20 ~ 30 m