

PRO 9545A3B-PA – 4MP Varomas 2,8-12 mm
dirbtinio intelekto bokšto IP kamera
su aktyvia atgrasinimo priemone,
įspėjimo žinute ir dviem kryptimis
garso transliacija



Alarm Inputs / Relay Outputs	1CH alarm input; 1CH alarm output
Audio Inputs	1CH audio input; 1CH built-in speaker; 1CH built-in MIC
BLC	Yes
BLC/SSDR (WDR)	120dB
Compression Method	Smart H.265 / H.265+ / H.265 / Smart H.264 / H.264+ / H.264 / MJPEG
DNR	3D DNR
Dimensions	Ø111.5 × 99.6

Image Sensor (CCD)	1 / 3" CMOS
Lens	2.8~12mm@F1.4, motorized
Minimum Illumination – Colour	0.0028 lux
Minimum Illumination – Mono	0 lux with IR
Operating Temperature	- 30 °C ~ 60 °C (-22°F~140°F)
POE	Yes
Power Consumption	< 11W
Power Source	DC12V/PoE
Remote Interface	Web Client/NVR/NVMS2.0/Mobile APP
Resolution (Best)	4MP (2592 × 1520)
Shutter	1 s ~ 1 / 100000 s
Storage Media & Capacity	Built-in micro SD card slot; up to 256GB
Weight(Cameras)	Approx. 0.64KG
Within Range of IR LEDs	30 ~ 50 m