

**PRO 9551S2 – 5 Megapikselių H.265 IR 3
srautas išorinė, atspari vandaliams,
burbulo stiliaus kamera – 3,6 mm.**



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	WDR
BLC/SSDR (WDR)	True WDR – 120db
Communication System	IP
Connection Cable	DC + POE / Video (RJ45) & (BNC),
DNR	3D + 2D
Dimensions	Width – 116mm – Height – 91mm
Dual Streaming	Yes + Triple Streaming
Effective Pixel	2592 × 1944
Gamma Correction	0.45
Horizontal Resolution	2592 × 1944
IR Illumination	0.05 lux @F1.2, AGC ON; 0 lux with IR
Image Sensor (CCD)	1/3" 5MP

Lens	3.6mm 5 Megapixel Day / Night Lens
Lens Mount	M12
Minimum Illumination – Colour	0.05 lux @F1.2, AGC ON
Minimum Illumination – Mono	0 lux with IR LEDs On
Model	IPC9551S2
P0E	Yes
Power Consumption	2.5W or 5W with IR on
Power Source	12V DC Regulated or P0E
S/N Ratio	55db +
Scanning System	PAL
Shutter	Auto
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP + Composite
Within Range of IR LEDs	10m – 20m