

PRO 9553E2A 5 Megapikselių H.265
3,3–12 mm motorizuotas realaus laiko
infraraudonųjų spindulių 3 srautas
išorinė, atspari vandaliams burbulo
stiliaus kamera – veido atpažinimas.



AES	–
AGC	Auto
AGC/Digital Sense up	–
Accessories Available	Yes
Aperture Correction	H aperture V aperture
Auto Flip	–
BLC	WDR
BLC/SSDR (WDR)	True WDR
Communication System	IP
Connection Cable	DC + POE / Video (RJ45) & (BNC), Audio in / out

Control Capability	–
DNR	3D
Dimensions	Width – 150mm – Height – 114mm
Dual Streaming	Yes + Triple Streaming
Enhancement	–
Gamma Correction	0.45
Horizontal Resolution	2592×1944
IR Illumination	30pc LED
Image Sensor (CCD)	5 Megapixel
Joystick Control	–
LCD Screen	–
Lens	3.3~12mm Megapixel Day / Night Lens
Lens (Digital)	–
Lens (Optical)	3.3~12mm
Lens Facilities	Varifocal
Lens Mount	–
Minimum Illumination – Colour	0.1 Lux
Minimum Illumination – Mono	0 Lux with IR LED's on
Model	5 Megapixel – 3.3~12mm Varifocal lens, True WDR True Day Night, Vandal Resistant, Audio, Triple Stream 12V DC or POE.
POE	Yes
Power Consumption	2.5W or 5W with IR on
Power Source	12V DC Regulated or POE
S/N Ratio	52db +
Scanning System	PAL
Shutter	Auto
Sync System	2:1 Internal
Sync. Type	Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP + Composite
Weight(Cameras)	1kg
Within Range of IR LEDs	25m