

PRO 9584C2B-PA – NAUJA!! PILNŲ SPALVŲ 8MP 4K 2,8 mm 3-in-1 Aktyvioji Atgrasinimo Turret Kamera



Audio Inputs	1CH audio input; 1CH built-in speaker; 1CH built-in MIC
BLC	Yes
BLC/SSDR (WDR)	120dB
DNR	2D/3D DNR
Dimensions	Φ 94.6 × 82.8
Image Sensor (CCD)	1 / 1.8" CMOS
Lens	2.8mm@F1.6, H.FoV:109°;V.FoV:57°;D.FoV:132°;
Lens Mount	M12
Minimum Illumination – Colour	0.008lux@F1.6,AGC ON,, 0 lux with LED
Minimum Illumination – Mono	0.008lux@F1.6,AGC ON, 0 lux with IR

Operating Temperature	– 30 °C ~ 65°C
P0E	Yes
Power Consumption	< 11.5W
Resolution (Best)	8MP(3840×2160)
S/N Ratio	≥50dB
Shutter	1 / 2s ~ 1 / 100000 s
Storage Media & Capacity	Built-in micro SD card slot; up to 256GB
Weight(Cameras)	Approx. 0.47KG
Within Range of IR LEDs	IR range: 20 ~ 30 m White light range: 20 ~ 30 m