

**PRO 9584E2G – SPECIALI KAINA – KOL YRA**  
**SANDĖLYJE – 4K 8MP H.265 IP Mini Akies**  
**rutuļys su IR LED, WDR, Daugiažeminis**  
**srautas su įmontuotu garso atpažinimu**  
**– Veido atpažinimas**



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
Audio Inputs	MIC IN x 1 built-in MIC x1
BLC	Yes
BLC/SSDR (WDR)	True WDR – 120dB
Communication System	IP
Compression Method	H.265/H.264 / MJPEG
Connection Cable	DC + POE / Video (RJ45) & (BNC)
DNR	3D NR
Dimensions	Ø 94.6mm×82.8mm
Dual Streaming	Support three streams
Effective Pixel	3840 x 2160
Gamma Correction	0.45
Gross Weight	Approx. 0.45KG

IR Illumination	up to 30m
Image Record Rate	Real Time
Image Sensor (CCD)	1/2.5" 8 Megapixel
Lens	2.8mm
Minimum Illumination – Colour	0.024 lux @ F1.2, AGC ON;
Minimum Illumination – Mono	0 lux with IR
Model	IPC9584E2
POE	Yes
Power Consumption	<6W
Power Source	12V DC Regulated or POE
S/N Ratio	55db+
Scanning System	PAL
Shutter	Auto
Storage Media & Capacity	Network remote storage □ micro SD card storage
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP + Composite
Within Range of IR LEDs	up to 30m