

PRO 9584S3B-2.8 – NAUJAS 4K 8MP
patobulintas IP mini akies kamuolys su
infraraudonaisiais LED ir įmontuotu
garso įrašu



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	IP
Compression Method	H.265/H.264 / MJPEG
Connection Cable	DC + POE
DNR	2D/3D DNR
Dimensions	Ø 94.6mm×82.8mm
Dual Streaming	Support three streams
Effective Pixel	3840 x 2160
Gamma Correction	0.45

Gross Weight	Approx. 0.45KG
IR Illumination	Up to 30m
Image Sensor (CCD)	1/2.5" 8 Megapixel
Lens	3.6 mm @F1.6, horizontal field of view: 87.7°
Minimum Illumination – Colour	0.024 lux @F1.2, AGC ON
Minimum Illumination – Mono	0 lux with IR
Model	9584S2
P0E	Yes
Power Consumption	<6W
Power Source	12V DC Regulated or P0E
S/N Ratio	55db +
Scanning System	PAL
Shutter	Auto
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Within Range of IR LEDs	Up to 30m