

PRO 9585E3L – 4K 8MP 2.8-12 mm
motorizuotas priartinimo objektyvas
H.265 IP mini akies rutulys su
įmontuotu garso įrašu – veido
atpažinimas



AES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
Audio Inputs	MIC IN x 1□built-in MIC x1
BLC	Yes
BLC/SSDR (WDR)	True WDR – 120dB
Communication System	IP
Compression Method	H.265/H.264 / MJPEG
Connection Cable	DC + POE / Video (RJ45) & (BNC)

DNR	3D NR
Dimensions	ø111.5 x 99.6mm
Dual Streaming	Support three streams
Effective Pixel	3840 x 2160
Gamma Correction	0.45
Gross Weight	Approx. 0.67 KG
IR Illumination	30-50m
Image Record Rate	20FPS
Image Sensor (CCD)	1/2.5" 8 Megapixel
Lens	Motorized zoom Lens 2.8~12mm
Minimum Illumination – Colour	0.024 lux @ F1.2, AGC ON;
Minimum Illumination – Mono	0 lux with IR
Model	FV-PR0 9585E2
P0E	Yes
Power Consumption	<9.5W
Power Source	12V DC Regulated or P0E
S/N Ratio	55db +
Scanning System	PAL
Shutter	Auto
Storage Media & Capacity	Network remote storage micro SD card storage
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP + Composite
Within Range of IR LEDs	30-50 metres