

PRO 9585S – 4K 8MP 2.8-12 mm varomasis priartinimo objektyvas H.265 IP mini kamerai „Eyeball”



aES	Yes
AGC	Auto
Aperture Correction	H aperture V aperture
BLC	Yes
BLC/SSDR (WDR)	Digital WDR
Communication System	IP
Compression Method	H.265/H.264 / MJPEG
Connection Cable	DC + POE
DNR	2D/3D DNR
Dimensions	φ111.5 x 99.6mm
Dual Streaming	Support three streams
Effective Pixel	3840 x 2160

Gamma Correction	0.45
Gross Weight	Approx. 0.67 KG
IR Illumination	30-50m
Image Record Rate	20 FPS
Image Sensor (CCD)	1/2.5" 8 Megapixel
Lens	Motorized zoom Lens 3.3~12mm @ F1.4, horizontal field of view:97.5°~38.5°
Minimum Illumination – Colour	0.024 lux @ F1.2, AGC ON;
Minimum Illumination – Mono	0 lux with IR
Model	IPC9585S2
POE	Yes
Power Consumption	<9.5W
Power Source	12V DC Regulated or POE
S/N Ratio	55db +
Scanning System	PAL
Shutter	Auto
Storage Media & Capacity	Network remote storage
Sync System	2:1 Internal
Video Output Signal	1.0vp-p, 75 ohm composite
Video output	IP + Composite
Within Range of IR LEDs	30-50 metres