

**PRO IPC8843IM – 4 Megapikselių 37x
priartinimas 500 m infraraudonųjų
spindulių diapazonas Automatinis
sekimas Greito kupolo maitinimo
šaltinis ir sieninis laikiklis
įtraukti.**



Alarm Inputs / Relay Outputs	7CH alarm input; 2CH alarm output
Audio Inputs	1CH audio input, 1CH audio output
BLC	Yes
BLC/SSDR (WDR)	120dB
Compression Method	H.265 / H.264 / MJPEG
DNR	3D Auto/Manual
Dimensions	Φ 278mm × 435mm (Φ 1094" ×17.12")
Image Sensor (CCD)	1 / 1.8 „progressive scan CMOS
Lens	f=5.6-208mm, 37x optical zoom
Lens (Digital)	16 x

Lens (Optical)	37 x
Minimum Illumination – Colour	0.005 lux @F1.5,
Minimum Illumination – Mono	0.001 lux @F1.5, 0 lux with laser IRs
Model	IPC8843IM
Presets	360
Privacy	24 programmable privacy masks
Resolution (Best)	4MP
Shutter	50Hz: 1 / 1 s ~ 1 / 25, 000 s; 60Hz: 1 / 1 s ~ 1 / 30, 000 s
Storage Media & Capacity	Built-in memory card slot, support microSD/SDHC/SDXC, up to 256G
Weight(Cameras)	Approx. 8.8KG(19.4lb)
Within Range of IR LEDs	500 metres